

SAFETY DATA SHEET  
**HydroBlok 1100 Primer  
400 Square Foot Kit**

**Part 1: Product and Company Identification**

Date Prepared: May 10, 2022  
Product Name: HydroBlok MVB Primer 1100  
Description/Use: Two component coating to be applied over concrete slabs  
Chemical Classification: Modified epoxy with additives  
Manufacturer: AYP Nano Solutions Inc.  
505 S. Villareal Drive Suite 206  
Anaheim, CA 92807 USA  
Chemtrec 1-800-424-9300  
Emergency Contact:

**Part 2: Hazards**



H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause allergic skin reaction.  
H351 Suspected of causing cancer.  
H411 Toxic to aquatic life with long lasting effects.

**Part 3: Composition on Ingredients**

<u>Ingredient</u>	<u>CAS</u>	<u>Per Cent</u>
Modified Bisphenol A epoxy	Closed	Closed
Proprietary trade secret	Closed	Closed
Titanium dioxide	13463-67-7	1 - 2%
Acetone	67-64-1	20 - 30%

**Part 4: Routes of Exposure & First Aid**

Eye Contact: Immediately flush eyes with plenty of water. Remove contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.

Skin Contact: Wash with plenty of soap and water. Continue to rinse for at least 20 minutes. Get medical attention.

Inhalation: Remove victim to fresh air and keep at rest in a comfortable position. If not breathing, or if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Ingestion: Wash out mouth with water. Remove victim to fresh air and keep in a comfortable rest position. If the victim is conscious, give small amounts of water to drink. Stop if the victim feels sick as vomiting may be dangerous. If vomiting occurs, head should be kept low so that the vomit does not enter the lungs. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

#### Part 5: Health Effects

##### Acute Health Effects:

Eye Contact: Causes serious eye irritation.  
Inhalation: No known significant effects or critical hazards.  
Skin Contact: Causes skin irritation.  
Ingestion: No known significant effects or critical hazards.

##### Chronic Health Effects:

Eye Contact: Adverse symptoms may include pain or irritation, watering and redness.  
Inhalation: No known significant effects or critical hazards.  
Skin Contact: Adverse symptoms may include irritation and redness.  
Ingestion: No known significant effects or critical hazards.

#### Part 6: Fire Fighting Measures

Flammability: Flammable liquid Class 1B  
Flash Point: 4°F  
Upper Explosive Limit: 27%  
Lower Explosive Limit: 3%  
Suitable Extinguishing Media: CO<sub>2</sub>, foam, dry chemical and water.  
Fire Fighting Measures: Cool containers with water to prevent pressure build-up. Wear full protective equipment and NIOSH full-contained breathing apparatus.  
Specific Hazards: Toxic to aquatic life. Fire water must be contained and prevented from discharge into waterways, sewers or drains.

#### Part 7: Accidental Release Measures

Spill & Leak Measures: Stop leak if without risk. Move containers from spill area. Contain and collect spillage with non-combustible absorbent material (sand, earth, vermiculite, diatomaceous earth) and place in container for disposal in accordance with regulations, both Federal and local.  
Specific Hazards: Toxic to aquatic life. Spill must be contained and prevented from discharge into waterways, sewers or drains.

#### Part 8: Handling and Storage

Storage: Store in accordance with local regulations. Store in original containers protected from direct sunlight in a dry, cool and well-ventilated area. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright.

#### Part 9: Personal Protection

Exposure Limits: Modified Bisphenol A epoxy, none.  
Titanium dioxide: ACGIH TLV TWA 10 mg/m<sup>3</sup> 8 hrs.  
Acetone: TWA PEL 8 hr, 750 ppm.  
Appropriate Engineering Controls: If operations generate dust, fumes, gas or vapor, use enclosures or local exhaust ventilation.  
Individual Protective Measures:

- Hygiene Measures before: Wash hands and forearms after use. Wash contaminated clothing before reuse.
- Eye/face Protection: Wear protective eyewear for splashes of product.
- Hand Protection: Wear chemical resistant gloves.
- Body Protection: Wear appropriate protective clothing based upon the tasks to be performed.
- Feet Protection: Wear non-slip and chemical resistant footwear.
- Respiratory Protection: Based upon the circumstances and need, select a respirator that meets the appropriate standards.

**Part 10: Physical and Chemical Properties**

- Physical State: Viscous liquid
- Color: Light grey when mixed
- Odor: Mild, epoxy
- VOC: None
- Density: 1.2
- Boiling Point: 133°F - 350°F

**Part 11: Stability and Reactivity**

- Reactivity and Chemical Stability: Stable under normal conditions
- Conditions to Avoid: No specific data.
- Hazardous Decomposition: None under normal storage and use. When there is a fire, decomposition products may include carbon dioxide, carbon monoxide, halogenated compounds, metal oxides.
- Incompatible Materials: Oxidizing materials.

**Part 12: Toxicological Information**

- Specific Organ Toxicity: For repeated exposure. No data available.
- Aspiration Hazard: No data available.
- Potential Acute Health Effects:
- Eye Contact: Causes serious eye irritation.
  - Inhalation: No known significant hazards.
  - Skin Contact: Cause skin irritation.
  - Ingestion: No known significant hazards.
- Symptoms:
- Eye Contact: Pain, irritation, watering, redness.
  - Inhalation: No known significant hazards.
  - Skin Contact: Irritation, redness.
  - Ingestion: No known significant hazards.
- Chronic Effects:
- Short Term Exposure: No known significant hazards.
  - Long Term Exposure: No known significant hazards.
  - Chronic Effects: Carcinogenicity: Suspected of causing cancer.  
Mutagenicity: No known significant hazards.  
Teratogenicity: No known significant hazards.  
Developmental effects: No known significant hazards.  
Fertility effects: No known significant hazards.

**Part 13: Ecological Information**

- Toxicity: Acetone: LD50 Dermal >9400 uL/kg (guinea pig); LD50 Oral 5800 mg/kg (rat).  
Titanium dioxide, Acute LC50>1,000,000 ug/L, marine water, 96 hrs.
- Persistence and Degradability: No data available.
- Mobility in Soil: No data available.

**Part 14: Disposal Considerations**

- Disposal Method: Dispose in accordance with Federal, State and Local regulations.

**Part 15: Transportation Information**

- DOT: Paint related material 3.
- Hazard Class: Class 3, PG II, limited quantity.
- UN Number: UN 1263.

**Part 16: Regulatory Information**

U.S. Federal:	All components are listed or exempted on TSCA 8b.	
SARA 311/312:	SKIN CORROSION/IRRITATION	Category 2
	SERIOUS EYE DAMAGE/IRRITATION	Category 2A
	SKIN SENSITIZATION	Category 1
	CARCINOGENICITY	Category 2
USA Hazardous Materials Info:	HEALTH	2
	FLAMMABILITY	1B
	PHYSICAL HAZARDS	0

**Disclaimer of Liability**

This document is generated for the purpose of distributing known health, safety and environmental information. It is not a specification sheet, nor should any displayed data be construed as a specification. Information was obtained from sources that we believe are accurate and reliable. The conditions or methods of handling, storage, use or disposal are beyond our control. For this and any other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the material.